

Installation Operation and Maintenance Manual

GENERAL INSTRUCTIONS NON-RETURN VALVE



THIS DOCUMENT is applicable to all Non-Return Valves (NRV). For service instructions specific to your product, please refer to the product specific manual and datasheet.

DESCRIPTION.

Non-Return Valves only allow flow in one direction. All BiS Wells NRV's are suitable for both hydraulic and pneumatic applications. Inside the NRV is a spring-loaded poppet and an elastomeric or polymer seat.

The standard inlet and outlet ports are stated in the installation drawing, alternative thread sizes and forms can be supplied.

For Maximum Working Pressure and other information, please refer to the product specific datasheet.

Note: 'Non-Return Valves' are also known as and can be referred to as 'Check Valves'.

PERFORMANCE DATA.

The maximum flow rate, and flow performance under given criteria through the NRV can be supplied by BiS Wells Ltd. See valve datasheet / installation drawing for capacity factor (Cv).

CONSTRUCTION.

The standard valve is constructed using aluminium alloy and brass. Alternative materials such as brass, bronze and stainless steel are available.

INSTALLATION, OPERATION AND MAINTENANCE

IMPORTANT

1. Products must not be modified in any way.
2. Do not use a valve if you suspect it leaks or if its performance is hindered in some way. The valve must be removed from the line and serviced accordingly.
3. Ensure that these instructions are made available to the operator or end user.

INSTALLATION.

Please ensure these instructions are read and understood before installing your product.

1. Only trained and experienced personnel should install this product.
2. Poor installation of the product can cause death or serious injury.
3. Consult the product specific datasheet for flow direction, mounting points and other information.
4. Always check that the system medium is compatible with the wetted valve materials.
5. Always check that the external valve materials are suitable for the ambient conditions.
6. NRV's can be installed in any orientation.
7. Thread lubricants and/or sealants must be used on tapered threads.
8. Gas or Fluid cleanliness is vital to ensure optimum performance and prolonged valve life.
9. Pressure supplied to the valve must be isolated before installation, and when installing gauges and similar components.
10. It is recommended that a safety relief valve is positioned downstream of the NRV.
11. All parallel female and male threads are designed to accept a bonded seal.
12. A 25-micron filter is recommended on the inlet supply to avoid damage to the valve seat from debris and other potential contamination. This is most advisable on new installations.

MAINTENANCE

Please ensure these instructions are read and understood before maintaining your product.

1. Only trained and experienced personnel should service this product.
2. Poor service of the product can cause death or serious injury.
3. Before maintenance work is undertaken, it is vital that any pressure stored within the valve is vented.
4. Valves can be returned to BiS Wells Ltd for maintenance and service.
5. Spares kits are available for purchase. When ordering spares kits please state model and serial numbers of the valve and, if possible, the gas or fluid in the system.
6. It is advisable to hold a Spares Kit for planned maintenance.
7. All maintenance work undertaken should be carried out in clean conditions.
8. Service intervals are the responsibility of the user.
9. A preventative maintenance plan should be put in place to ensure safe and continuous operation.
10. If a filter has been fitted upstream of the valve it should be regularly cleaned or replaced.
11. Only use lubricants compatible with the valves materials of construction and the system medium.

OPERATION

Please ensure these instructions are read and understood before using your product.

1. During use ensure the maximum working pressure (MWP) is not exceeded. MWP is marked on the valve / tag and, also on the product specific datasheet. If unsure, please contact BiS Wells Ltd.
2. Misuse of the product can cause death or serious injury.
3. Regularly inspect the product for signs of damage before use.
4. Apply pressure in a controlled manner. Pressure spikes and/or shocks must be avoided.
5. Gas or Fluid cleanliness is vital to ensure optimum performance and prolonged valve life.
6. Remove excess moisture from the gas. Excess moisture can cause icing.
7. Ensure that vented fluids and gasses are done so in a safe and controlled manner. Some gasses can cause suffocation.